

CenturionDoor

Chubbsafes
Trusted the world over.

PRODUCT SPECIFICATION

Grade	Number of bolts	Total Weight (kg)	Total thickness of door (mm)	Clear opening H x W (mm)
<i>Euro V</i>	6	1700	290	1970 x 900
<i>Euro VI</i>	6	1700	290	1970 x 900
<i>Euro VII</i>	6	1700	290	1970 x 900
<i>Euro VIII</i>	6	1700	290	1970 x 900
<i>Euro IX</i>	6	1700	290	1970 x 900
<i>Euro IX KB</i>	6	1700	290	1970 x 900
<i>Euro X</i>	6	3000	415	1970 x 900
<i>Euro X KB</i>	6	3000	415	1970 x 900
<i>Euro XI</i>	6	3000	415	1970 x 900
<i>Euro XI KB</i>	6	3000	415	1970 x 900
<i>Euro XII</i>	10	3000	415	1970 x 900
<i>Euro XII KB</i>	10	3000	415	1970 x 900

CenturionDoor

KEY FEATURES:

- High quality protection using modern high specification materials and technology.
- Provide the highest level of protection against thermal and mechanical attack.
- Manufactured to correspond with the latest security standards.
- Designed specifically to suit your security needs.
- Available in a range of security grades.



Chubbsafes
Trusted the world over.

PO Box 61, Woden Road, Wolverhampton, WV10 0EW United Kingdom
Tel. +44 (0) 1902 455111 Fax: +44 (0) 1902 351961
Email: marketing@chubbsafesuk.com
Website: www.chubbsafes.com

'Chubb' is owned by Chubb plc and is a registered trademark used under license

Vault doors - optimum security using lock and key

The importance of locking and accessing a room cannot be understated. This is nowhere more important than with a vault room. A vault room door must provide the highest level of protection whilst allowing flexible and efficient access for authorised persons. Such product characteristics, as well as many others, are found in the Chubb safes Centurion door. Designed specifically to secure the Centurion vault room, the Centurion door has evolved after years of product development. On purchasing the door, you can be assured that your investment will be reflected in the product quality and customer care received from Chubb safes. After all, Chubb safes are trusted the world over!!!

CenturionDoor

QUALITY FEATURES:

Testing:

The vault room doors are certified and tested by the Association of Property Insurers (VdS) in Cologne. Such processes are done in accordance with the European test regulations developed by the responsible EU bodies.

Construction:

The Centurion room door consists of a door frame, grille gate and the main strong room door.

Door frame:

The frame consists a heavy box frame surround which is reinforced with special armour components. It is then integrated into the skin of the vault room thus completing the vault room framework.

Grille gate/day door:

This mechanically or electrically operated hinged gate provides further security to the main door. It is available in mild steel or glass. The gate is secured via a high security lock.

Main strong room door:

The door is manufactured to the same security standard as the vault. The barrier material is of reinforced concrete matrix. The door is secured in the frame, by 6 rectangular steel bolts to the leading edge of the door.

High security locking:

The Centurion doors come supplied with 1 keylock and 1 numeric combination lock (up to grade Euro XKB) as standard. Grades above this benefit from an extra numeric combination lock. Other locking configurations can be specified to suit customer requirements.

CUSTOMISATION:

Chubb safes can customise the Centurion door to meet your specific security needs. Options available are as follows:

Safelock:

The standard locking supplied with the door can be replaced with the Safelock. This high security electronic lock has an extensive range of features which are as follows:

- Protected code entry.
- Automatic recording.
- Timelock function.
- Time delay.
- Remote release of external motoring.
- Silent alarm.
- Arms and disarms EMA .
- Allows multiple users - maximum of 10.
- User management.

Alarm system:

The door can be prepared for use with an alarm system. This includes an invisible alarm cable entry and a mounting plate onto which an alarm system can be placed. For further details please ask consultant for guidance.

DESIGN FEATURES:

Size:

The Centurion door is available in standard widths of 900mm, 1225mm and 1500mm clear openings. Standard door height is 1970mm clear opening. Other sizes are available on request.

Finish:

The door can be finished in painted topcoat to customer specification. Other finishes are available.

WORKING WITH YOU:

PLANNING AND CONCEPTION:

Centurion doors are normally provided alongside the purchase of a Centurion vault room. Hence, the door is selected and scheduled in line with the vault room project. Where a Centurion door is to be incorporated into a masonry/cast concrete strongroom, a special grip frame is manufactured to suit wall thickness. Our Chubb safes consultant will advise where necessary.

INSTALLATION - THE COMPLETE SERVICE:

The Centurion door is delivered and installed by trained Chubb safes installation teams after the completion of the vault room. Prior to installation, a full and comprehensive installation survey will be undertaken and incorporated into any proposal.

The flexibility of the installation process is evidence of Chubb safes commitment towards ensuring the cost and time efficient completion of your project. Throughout the process our Chubb safes consultant will be on hand to discuss all aspects of your project.

